

Remove smells & bacteria with a single unit

Simple to install, this low maintenance, perfect for safely removing odours and airborne bacteria.

The LoBact 10 utilises plasma ionisation technology to destroy odours & bacteria present in ambient air. It is suitable for a range of environments such as restaurant kitchens, refuse storage and public waiting areas.

Simple to install, with low maintenance and running costs, this versatile solution provides affordable and reliable odour & bacteria control, making it the perfect partner for a wide range of applications.



Benefits

- Low capital and running costs
- Simple installation and maintenance
- Aesthetic design
- Compact, lightweight and robust
- Quiet operation
- Environmentally friendly

*Continuously improving its products and services and reserves the right to alter designs without prior notice



**Kitchen
Flow
Solutions**



CPD



T: 0121 293 0800
sales@kitchenflowsolutions.co.uk
www.kitchenflowsolutions.co.uk

Odour & Bacteria Control from LoBact

The LoBact utilises plasma ionisation technology, also known as Bipolar Ionisation, to destroy odours present in ambient air. The LoBact 10 is suitable for a range of environments such as restaurant kitchens, refuse storage and public waiting areas.

Simple to install, with low maintenance and running costs, this versatile modular solution provides affordable and reliable control, making it the perfect partner for a wide range of applications.

Odour Control from LoBact Air

The LoBact is designed to inject charged ions including activated oxygen into rooms of up to 100m² to destroy odours in ambient air. It works by oxidising nuisance smells, leaving the air smelling hygienically clean. The LoBact 10 is suitable for a range of environments such as refuse storage areas, washrooms, hotel rooms, care homes and public waiting areas.

Installation

The LoBact is a plug and play system which is simply mounted on the wall, adjacent to the source of the problem.

Accessories

Spare pre-filters

Maintenance

Over time and dependent on the installation environment, the prefilter of the LoBact 10 can be simply changed. The ionisation tubes are also to be inspected and can be easily cleaned. Both filters and ionisers should be exchanged at regular intervals, depending on site factors.

Warranty

1 year Manufacturer's Warranty ([subject to terms and conditions](#))

Extended 3 year Warranty ([care plan available](#))

Terms

In accordance with our standard terms of business.

Technical Specifications & Data

Dimensions (HWD)	300 x 305 x 100mm
Operation	Adjustable Timer
Power	Up to 45W
Power Supply	230Vac/ 1 phase / 50-60Hz
Weight	4kg
Finish	Grade 304 stainless steel
Mounting	Wall or surface mounted
Approvals	LoBact air cleaners comply with current CE requirements and EMC standards. Certifications are available on request.



*Continuously improving its products and services and reserves the right to alter designs without prior notice



**Kitchen
Flow
Solutions**



T: 0121 293 0800
sales@kitchenflowsolutions.co.uk
www.kitchenflowsolutions.co.uk